


ELECTRONIC CHARGERS

SPI1224 ⚡ 12/24 V 🔌 15/10 A



+++

For 12 V or 24 V batteries up to 230 Ah

Microprocessor controlled and multi-stage charging

Protection against: Reverse polarity, spark proof and thermal runaway. Safety shut-off and ventilation system

AGM, gel, calcium, Start n' Stop

Charging status Led

Hook attachment and protective bumpers

Multilingual digital display

Recovery mode for sulphated batteries for 12 and 24 V



THE SPI RANGE



SPI1

SPI2

SPI3

SPI6

SPI10

SPI15

SPI1224

TECHNICAL INFORMATION

MODEL	SPI1	SPI2	SPI3	SPI6	SPI10	SPI15	SPI1224
PART NUMBER	94065104*	94065049*	94065050*	94065091*	94065092*	94065189*	94065194*
	* Add letter plug type PLUG EU = C PLUG UK = G PLUG AU = I						
OUTPUT VOLTAGE (DC)	6/12 V	6/12 V	12 V	12 V	12 V	12 V	12/24 V
NOMINAL AC VOLTAGE	230V AC - 50 Hz						
MAX. CHARGING CURRENT	1 A	2 A	3 A	6 A	10 A	15 A	15/10 A
IP RATING	IP54	IP54	IP54	IP20	IP20	IP20	IP20
BATTERY TYPE	Lead-Acid	Lead-Acid	Lead-Acid & Lithium	Lead-Acid	Lead-Acid	Lead-Acid	Lead-Acid
OUTPUT CABLE (CM) (FROM ENCLOSURE TO CLAMP END)	201	185	185	218	218	185	185
WORKING TEMPERATURE	-20° to +50° C						



PACKAGING INFORMATION

MODEL	SPI1	SPI2	SPI3	SPI6	SPI10	SPI15	SPI1224
NET WEIGHT	0,6 kg	1 kg	1 kg	1,4 kg	1,4 kg	1,7 kg	1,7 kg
DIMENSIONS (L x W x h) mm	195 x 148 x 65	189 x 210 x 77	189 x 210 x 77	208 x 83 x 239	208 x 83 x 239	228 x 102 x 244	228 x 102 x 244

HOW TO CHOOSE

PART NUMBER	MODEL	VOLTAGE	6 V	12 V							24 V		
			12 Ah	32 Ah	46 Ah	58 Ah	130 Ah	165 Ah	200 Ah	230 Ah	230 Ah	360 Ah	550 Ah
94065104	SPI1	6/12 V	■	■									
94065049	SPI2	6/12 V	■	■	■								
94065050	SPI3	12 V		■	■	■							
94065091	SPI6	12 V		■	■	■	■						
94065092	SPI10	12 V		■	■	■	■	■	■				
94065189	SPI15	12 V		■	■	■	■	■	■	■			
94065194	SPI1224	12/24 V		■	■	■	■	■	■	■	■		