



ELECTRONIC CHARGERS

SPI25 PRO ⚡ 12/24 V 🔌 25/12,5 A



+++

Showroom mode

GEL - WET - AGM - VRLA - MF - DRY - Start'n Stop

Compatible lithium LiFePO4

Charge amperage selection

Power supply - Memory saver

ADAS supply

Recovery mode

Standard accessories: clamps





SPI16 PRO

SPI25 PRO

TECHNICAL INFORMATION

MODEL	SPI16 PRO	SPI25 PRO
PART NUMBER EUROPE	809030	809040
PART NUMBER AUSTRALIA	94065316I	94065325I
VOLTAGE (DC)	12 V - 24 V	12 V - 24 V
NOMINAL AC VOLTAGE	230V AC - 50 Hz	230V AC - 50 Hz
INPUT POWER	280 W	450 W
RATED CURRENT (MIN-MAX)	4 - 8 -16 A	5 - 12,5 - 25 A
CHARGING AND TESTING STAGES	9	9
CHARGE CAPACITY	5 Ah - 360 Ah	5 Ah - 550 Ah
MAINTENANCE CAPACITY	5 Ah - 550 Ah	5 Ah - 800 Ah
SHOWROOM FUNCTION	13,8 V - 13 A	13,8 V - 21 A
IP RATING	IP20	IP20
WORKING TEMPERATURE	-20° to +50° C	-20° to +50° C



PACKAGING INFORMATION

MODEL	SPI16 PRO	SPI25 PRO
NET WEIGHT	2 kg	2,50 kg
DIMENSIONS (L x W x h) mm	340 x 340 x 10	340 x 340 x 10

? HOW TO CHOOSE

PART NUMBER	MODEL	VOLTAGE	6 V	12 V							24 V		
			12 Ah	32 Ah	46 Ah	58 Ah	130 Ah	165 Ah	200 Ah	230 Ah	230 Ah	360 Ah	550 Ah
809030	SPI 16 PRO	12/24 V		■	■	■	■	■	■	■	■	■	
809040	SPI 25 PRO	12/24 V		■	■	■	■	■	■	■	■	■	■