




ELECTRONIC CHARGERS

SPI3 ⚡ 12 V 🔌 3 A



+++

100% automatic battery charger and maintainer with safety shut-off

AGM, Standard, gel, calcium, Start n' Stop, Lithium (LiFePO₄)

For 12 V batteries up to 58 Ah

Compatible lithium LiFePO₄

Microprocessor controlled and multi-stage charging

Protective bumpers and hook attachment

Protection against: Reverse polarity, spark proof and thermal runaway

Multilingual digital display



THE SPI RANGE



SPI1

SPI2

SPI3

SPI6

SPI10

SPI15

SPI1224

TECHNICAL INFORMATION

MODEL	SPI1	SPI2	SPI3	SPI6	SPI10	SPI15	SPI1224
PART NUMBER	94065104*	94065049*	94065050*	94065091*	94065092*	94065189*	94065194*
	* Add letter plug type PLUG EU = C PLUG UK = G PLUG AU = I						
OUTPUT VOLTAGE (DC)	6/12 V	6/12 V	12 V	12 V	12 V	12 V	12/24 V
NOMINAL AC VOLTAGE	230V AC - 50 Hz						
MAX. CHARGING CURRENT	1 A	2 A	3 A	6 A	10 A	15 A	15/10 A
IP RATING	IP54	IP54	IP54	IP20	IP20	IP20	IP20
BATTERY TYPE	Lead-Acid	Lead-Acid	Lead-Acid & Lithium	Lead-Acid	Lead-Acid	Lead-Acid	Lead-Acid
OUTPUT CABLE (CM) (FROM ENCLOSURE TO CLAMP END)	201	185	185	218	218	185	185
WORKING TEMPERATURE	-20° to +50° C						



PACKAGING INFORMATION

MODEL	SPI1	SPI2	SPI3	SPI6	SPI10	SPI15	SPI1224
NET WEIGHT	0,6 kg	1 kg	1 kg	1,4 kg	1,4 kg	1,7 kg	1,7 kg
DIMENSIONS (L x W x h) mm	195 x 148 x 65	189 x 210 x 77	189 x 210 x 77	208 x 83 x 239	208 x 83 x 239	228 x 102 x 244	228 x 102 x 244

HOW TO CHOOSE

PART NUMBER	MODEL	VOLTAGE	6 V	12 V							24 V		
			12 Ah	32 Ah	46 Ah	58 Ah	130 Ah	165 Ah	200 Ah	230 Ah	230 Ah	360 Ah	550 Ah
94065104	SPI1	6/12 V	■	■									
94065049	SPI2	6/12 V	■	■	■								
94065050	SPI3	12 V		■	■	■							
94065091	SPI6	12 V		■	■	■	■						
94065092	SPI10	12 V		■	■	■	■	■	■				
94065189	SPI15	12 V		■	■	■	■	■	■	■			
94065194	SPI1224	12/24 V		■	■	■	■	■	■	■	■		